

*This walk-up, through-the-wall ATM is designed for high-traffic areas with the capacity to hold up to 6,000 notes. Plus, it offers true flexibility for future expansion.*

## **Features**

### **Powerful Transaction Support**

With the Microsoft Windows XP Platform and an Intel Pentium Processor, the Monimax 7000T guarantees support for both larger and faster transactions.

### **High Level of Scalability.**

Designed to support multi-vendor solutions, this ATM can easily support additional financial services, including an optional built-in check scanner, bill acceptor and envelope depository.

### **Reliability**

The Monimax 7000T satisfies demanding performance standards such as UL 291Level 1 and PCI-certified encrypting PIN pad.

***Superior quality, security and value.***

***Only with Nautilus Hyosung.***

*Now offering the most complete line of financial and retail ATMs.*



**The Monimax 7000T offers a customer-centric interface with the power to grow with your business.**

### **Dependable Customer Service**

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

# MONIMAX 7000T

## System Control

- Microsoft® Windows XP® platform
- Intel® Pentium®-IV processor

## Customer Display

- 10.4" TFT LCD
- Sunlight viewable

## Communication

- Dial-up
- TCP/IP (SSL configurable)

## Input Type

- 4 x 2 function keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

## Supervisor Operation

- 5.7" Mono display
- 4 x 4 numeric keys
- 4 x 2 function keys

## Card Handling

- Dip-type card reader
- Optional IC card reader, EMV Level 1, 2

## Cash Dispensing

- 2,000-note cassettes
- Optional cassettes (up to three)

## Depository

- Envelope depository

## Printers

- 3.1" graphical thermal receipt printer

## Security

- UL291 Level 1 safe
- Mechanical combination lock
- Optional electronic safe lock
- Optional KABA Mas Cencon safe lock

## Miscellaneous

- Lead-through indicator
- Illuminated signage

## Optional

- Heater
- Electronic journal

## Power Supply

- AC 110–230V, 50–60 Hz

## Operating Environment

- Temperature: -32°F–104°F
- Humidity: 25%–85%

## Dimension and Weight

- Height: 61.2" (1,548 mm)
- Width: 32.6" (830 mm)
- Depth: 38.6" (982 mm)
- Weight: 1,440 lbs (650 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



**Nautilus**  
HYOSUNG

Contact your authorized Nautilus Hyosung distributor or representative for more information.