

The Monimax 7600DR is the ideal choice for handling high-volume transactions with the capacity to hold up to 12,000 notes. It also offers the newest technology that accepts bundle-note or bundle-check deposits.

Features

Powerful Transaction Support

With the Microsoft Windows XP Platform and an Intel Pentium IV Processor, the Monimax 7600DR guarantees support for both larger and faster transactions, including envelope-free bundle check and bundle cash deposits.

Fully Upgradeable

The 7600DR lets you deploy deposit automation upgrades when your institution is ready.

Reliability

The Monimax 7600DR satisfies demanding performance standards such as a UL 291 Level 1 safe and PCI-certified encrypting PIN pad.

Superior quality, security and value.

Only with Nautilus Hyosung.

Now offering the most complete line of financial and retail ATMs.



Deposit automation saves you money by reducing your printing costs. Plus, you can save tons of paper over time, giving you the power to build your image as an earth friendly company.



The Monimax 7600DR offers the latest deposit automation technology. The upgradeable design allows it to grow with your business.

MONIMAX 7600DR

System Control

- Microsoft® Windows XP® platform
- Intel® Pentium®-IV processor
- NDC+, DDC912, User Application

Customer Display

- 15" color TFT LCD

Optional

- Privacy filter
- Sunlight readable

Communication

- TCP/IP (SSL configurable)

Optional

- Dial up, Wireless, X.25

Input Type

- PCI EPP (Encrypting PIN pad)
- ADA compliant

Optional

- Touch screen

Supervisor Operation

- 15" TFT color LCD, touch screen

Card Handling

- Dip-type card reader

Optional

- IC card reader EMV Level 1, 2 compliant
- Anti-skimming
- Motor-driven card reader

Cash Dispensing

- 3,000-notes cassette
Up to four cassettes
- Bundle retraction
- Automatic shutter

Depository

- Bundle check scanner and acceptor
- Bundle note acceptor

Optional

- Envelope depository

Printers

- 3.1" graphical thermal receipt printer
- 5,000 transaction receipt printer
- Electronic journal

Optional

- Journal printer

Security

- UL291 Level 1 safe
- Mechanical combination lock

Optional

- Electronic safe lock
- KABA Mas Cencon safe lock
- Security camera

Miscellaneous

- Lead-through indicator
- Illuminated signage

Optional

- Heater

Power Supply

- AC 110–240V, 50–60 Hz
- Back-up battery

Operating Environment

- Temperature: -31°F–104°F
- Humidity: 25%–85%

Dimension and Weight

- Height: 69.3" (1,760 mm)
- Width: 32.7" (831 mm)
- Depth: 40.6" (1,032 mm)
- Weight: 1,978 lbs (897 kg)



Nautilus
HYOSUNG

Contact your authorized Nautilus Hyosung distributor or representative for more information.