

The NH-1800 CE offers exceptional value with the power of a Microsoft® Windows® CE platform. Featuring a new topper design, it is also an attractive addition to any retail setting.

Features

Maximum Reliability

The 1800 CE is designed to provide industry leading quality and reliability with highest uptime rates. The 1800 CE is designed to require minimum maintenance and all Nautilus Hyosung ATMs are known for reliability and have a proven track record in the U.S. market.

Quick Pick Lotto Software Ready

The 1800 CE is capable of being loaded with Linq 3's proprietary Quick Pick Lotto software. Quick Pick Lotto capability can be upgraded to existing CE models already installed, or added to new ATMs you order.

Capacity up to 4,000 Notes

A variety of cash-dispensing configurations are available with a capacity of up to 4,000 notes. The 1800 CE is available with a 1,000 note removable cassette or optional 2,000 note removable cassette, upgradable to 2 cassettes.

Secure Communications

The 1800 CE comes with TCP/IP (SSL configurable) communication capability to support high-volume locations.



The 1800 CE is Quick Pick Lotto Software-enabled.

The NH-1800 CE is simply the best value in ATM solutions for the retail industry.

1800 CE

System Control

- Windows CE Platform
- Microsoft® Windows® CE

Customer Display

- 8" TFT LCD

Communication

- TCP/IP (SSL configurable)
- Dial-up (optional pre-dial function)

Input Type

- 4 x 2 function keys
- 4 x 4 numeric keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

Supports Three Languages

- English
- Spanish
- French

Supports Quick Pick Lotto Software



Card Handling

- Dip-type card reader
- Optional IC card reader,
EMV Level 1, 2 Compliant

Cash Dispensing

- 1,000-note removable cassette
- Optional 2,000-note removable
cassette can be upgraded to 2
cassettes for 4,000 notes

Printer

- 80 mm graphical thermal receipt printer

Security

- UL® Business Hour safe
- Mechanical combination lock
- Optional UL® Level 1 safe
- Optional electronic safe lock
- Optional KABA Mas Cencon safe lock

Power Supply

- AC 110–230V, 50–60 Hz

Operating Environment

- Temperature: 32°F–104°F
- Humidity: 20%–85%

Dimension and Weight

- Height: 51.3" (1,304 mm)
- With top: 65.3" (1,675 mm)
- Width: 15.7" (400 mm)
- Depth: 22.8" (580 mm)
- Weight: 265 lbs (120 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



Illuminated topper

8" color customer display
• Ad-capable: 6-screen (JPEG)

Key pad light

PCI PIN pad

ADA voice
guidance jack

Cash dispenser and
guide light indicator

ATM

Secure
Communications
Dial-up or
Built-in TCP/IP
and SSL

4 x 2 function keys

Receipt printer and
guide light indicator

Card reader and
guide light indicator

 NAUTILUS HYOSUNG

Contact your authorized Nautilus Hyosung distributor
or go to www.nhatm.com for more information.