



HYOSUNG

Full-Function, Through-The-Wall Drive-Up ATM

7600XLD

Designed to provide unprecedented reliability, the 7600 series is unparalleled in the market. The **7600XLD** through-the-wall drive-up ATM can easily be upgraded from a cash dispenser to deposit automation and supports large volume transactions. Its high uptime and minimum maintenance has helped make Hyosung the fastest growing ATM company in the US.

KEY FEATURES

HIGH AVAILABILITY

Innovative design and the use of Hyosung manufactured core technologies allows for fast, easy replenishment and reduced downtime.

The **7600XLD** is designed to provide reliability that is unequalled in the market, with minimum maintenance and maximum up time.

FLEXIBILITY

The 7600 series can also be easily upgraded from a cash dispenser to deposit automation should an institution decide to implement the technology later.

CAPACITY

High capacity, cash dispense capability and the ability to support large volume transactions, makes the **7600XLD** a high capacity machine.

SECURITY OPTIONS

Hyosung ATMs defend against physical and logical attacks with a multi-level locked down operating system, anti-skimming, white-listing, and encryption.



SPECIFICATIONS

DIMENSION

- Height: 54.4"
- Width: 28.4"
- Depth: 40.6"
- Weight: 1,978 lbs.

ENVIRONMENTAL

- Temperature: 32°F – 104°F (0°C~40°C)
- Humidity 25% – 85%

SOFTWARE

- Microsoft Windows® 7
- Windows10 ready

CUSTOMER INTERFACE

- 15" TFT LCD
- Input Method – Touch screen
- Privacy Filter – 15" filter
- PIN Pad – PCI compliant
- ADA audio guidance – earphone jack
- Card Reader – DIP, EMV compliant

MEDIA TECHNOLOGY

- **Dispense**
 - Configurable denominations up to 4 cassettes
 - 3,000 notes per cassette
 - Bundle present, bundle retract
- **Cash & Check InModule (CCIM)**
 - Maximum capacity 50 checks/cash per bundle per transaction
 - Check cassette capacity 2000 note (CCIM)
 - Cash cassette capacity 2000 note (CCIM)
 - Reject and retract capability

SECURITY

- Safe: UL291 Level 1
- Alarm – Seismic + Heat
- Locking Device – Electronic, mechanical combination lock, Kaba Mas Cencon lock (optional)
- Security camera

SERVICING

- Rear access
- State of health indicators across

PRINTER

- 3.1" graphical thermal receipt printer

ADDITIONAL INFORMATION

- Communication – TCP/IP
- Backup battery reserves the last transaction & safe shutdown

*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

Features and benefits are for U.S. configuration only. If located outside of the U.S., please contact sales.